

A Minor Project Report on

“SMACBOT”

**Bachelor of Engineering in
Mechanical Engineering**

Submitted by

Srivatsa Belgaumkar	01FE18BME143
Anirudh Gudi	01FE18BME183
Supreet Mudhol	01FE18BME184
DheerajsingRajaput	01FE18BME186
Vikhyat G	01FE18BME182
Vijay Kalyani	01FE18BME157

Under the Guidance of

Prof. Praveen Petkar

**K L E Society's
KLE Technological University
HUBLI-31
School of Mechanical Engineering**

CERTIFICATE

This is to certify that Capstone Project entitled **“SMACBOT”** (Smart Floor Mopping Device) submitted by **Team C7** to the **KLE Technological University**, Hubli-580031, towards partial fulfillment for the award of the degree of Bachelor of Engineering is a bona-fide record of work carried out by him/her under our supervision. The contents of project report, in full or in parts, have not been submitted to any other institute or university for award of any degree or diploma.

Prof. Praveen Petkar

Dr. B. B. Kotturshettar

Guide

Head of department

Name of the Examiners

Signature with date

- 1.
- 2.

ACKNOWLEDGEMENT

The successful completion of any task would be incomplete without mentioning the people who made it possible and whose guidance and encouragement has made our efforts successful.

At the outset, we would like to express our deep sense of gratitude for our guide **Prof. Praveen Petkar** for making this project report successful through their invaluable guidance at every stage of the project report.

We also thank **Dr. B. B. Kotturshettar** for his encouragement in undertaking the task of this project.

We express our sincere regard and gratitude to our project coordinators **Prof Nagaraj Ekbote, and Prof. Shridhar M**, School of Mechanical Engineering, KLE Technological University, Hubli

We also thankful to all faculty members of the Mechanical Engineering Department of KLE Technological University, for helping us directly or indirectly in different stages of our project work.

Students signature

(Team C7)

MINOR PROJECT TEMPLATES

Phase wise expectations and tasks:

Design Phase:

1. Refined problem statement		<i>(Tick mark the cell once each activity is completed)</i>
1.1	Identifying end users (Customers)	
1.2	Identify customer needs	
1.3	Analyzing the needs	
1.4	Requirements List	
2. Product benchmarking		
2.1	Studying and exploring competitive products	
2.2	Patent search	
2.3	Literature survey	
3. Design Specifications		
3.1	Objectives	
3.2	Constraints	
3.3	Objective tree (affinity diagram)	
3.4	Design Specifications	
4. Concept generation		
4.1	Defining Functions	
4.2	Morphological chart	
4.3	Generating design alternatives	
4.4	Selecting best alternatives (Pugh chart)	
5. Design		
5.1	3D Model	
5.2	Assembly models	
5.3	2D drawing	
5.4	Design Calculations	
6 Prototype Planning		
6.1	Raw materials	
6.2	Bill of Materials	
6.3	Joining techniques/ methods	
6.4	Flow Chart	
6.5	Sub-Assembly Planning	



Experience Engineering @
**School of Mechanical
EngineeringKLETECH**
— Engage | Explore | Excel | Evolve —



KLE Technological
University
Creating Value
Leveraging Knowledge

Phase 1

1 Refined problem statement

1.1 Identifying end users (Customers)

- Determine who the customers are for your product

1.2 Identify customer needs

- Determine what information should be gathered from customers, their needs, expectations

1.3 Analyzing the needs

- Determine how that information should be gathered

Customer: Nalini S. Interviewer(s): Supreet M. Date: 02/04/2021		
Question/Prompt	Customer Statement	Interpreted Need/ Expectations
Typical uses	Removing coffee/tea stains from the floor is difficult.	Proper Scrubbing of the floor is to be ensured
	I mop my floor with Phenyl added water.	Phenyl added water cleans better over normal water.
Likes-current methods followed(traditional techniques)	I can stress on more dirt accumulated areas.	Dirty area of the floor is to be cleaned effectively
	Visual inspection of the whole process will be available.	Process need to be visually inspected
Dislikes-current methods followed(traditional techniques)	Consumes a lot of time if the area is large.	Time span of the whole process should be reduced.
	It requires a lot of physical work	Minimal amount of physical work should be made possible
Suggested Improvements	Shouldn't damage the marble/granite flooring	Proper use of phenyl to be supervised
	Floor to be dried in short period of time	Quick dry.

Customer: Ramesh I. Interviewer(s): Vikhyat G. Date:06/04/2021		
Question/Prompt	Customer Statement	Interpreted Need/ Expectations
Typical uses	Corners, Area under furnitures end up not being well cleaned.	Every Part of the floor must be cleaned.
	Disinfectants should be used to clean the floor.	Propr disinfectant to be made sure
Likes-current methods followed(traditional techniques)	I would rather quick wipe my floor with mop to save time	shortly effective method to be used for time saving
	I prefer warm water over cold water.	Proper water temperature to be maintained.
Dislikes-current methods followed(traditional techniques)	Consumes lots of water	Water consumption should be reduced.
	Excessive use of Phenyl leads to damage on the floors.	Optimum amount of chemical to be used.
Suggested Improvements	Should consume less amount of time with effective cleaning.	Quick and effective cleaning to be maintained.
	The device must be easy to handle even for a common man.	User friendly and easily controllable.

1.4 Requirements List

Customers	Requirements
1 to 6	1. Quick and effective cleaning.
	2. Proper Disinfectant.
	3. User friendly
	4. Quick dry
	5. Should not corrode / decolourize the floor.

Phase 2

2. Product Benchmarking

2.1 Studying and exploring competitive products

Products (Images or name)	Specifications	Cost	Advantage	Limitations	Functions
iBell Robotic Vacuum Cleaner 	Name iBell Robotic Vacuum Cleaner Dimensions 436 X 368 X 11.8 Battery Capacity 3200mAh Wi-Fi 2.4GHz 802.11 b/g/n Running Time 60-130 minutes Weight 3.6kg Rated Power 33W Working Noise ≤70dB (Standard mode)	₹16,240	Effective, independent, all-purpose cleaning Decent battery life Very good app and features Laser Detect System for good navigation	Needs care and regular cleaning Doesn't reach edges and narrow gaps Can't replace manual vacuuming and mopping entirely	

EUFY by Anker 	Max Power Consumption 27W Battery Li-Ion Product Dimensions 32.5 X 32.5 X 7.2 Product weight 2.7 kgs	₹14,999	Moves quickly and has no trouble switching between floor Easy to set up and use Compact design with two large, spinning mopping pads Features a Hand Mode to clean types Eight floor-cleaning modes	No app or voice control Doesn't always avoid area rugs and carpeting	
--	--	----------------	--	--	--

3 ECOVACS Deebot 500 	Dimensions: 33.2 X 33 X. 7.9 Weight: 4.85 lbs Battery Type: Lithium Ion	₹13,900	Three mopping modes Automatically recognizes and avoids carpet Can clean in sequence with select Roomba robot vacuums	Too big for cleaning in tight spots in bathrooms and kitchens	
---	---	----------------	--	--	--

2.2 Patent search

Patent Name/ Number/ Date	Information
Robotic vacuum cleaner US10729297B2 Publication Date: 04/08/2020	A robotic vacuum cleaner having a nozzle inlet facing a surface to be cleaned, and a rotatable side brush. The rotatable side brush has bristles extending substantially in parallel with the surface to be cleaned, and the nozzle inlet includes a frame structure forming an opening, the opening being arranged in fluid communication with a debris receptacle. The bristles extend over a side portion of the nozzle inlet. The frame structure has a base portion extending substantially in parallel with the surface to be cleaned. The base portion extends at a first level. The frame structure at the side portion extends substantially in parallel with the surface to be cleaned at a second level. The first level is arranged closer to the surface to be cleaned than the second level.
Cylindrical robotic vacuum US9521934B1 Publication Date: 20/12/2016	A robotic vacuum wherein the housing of the system is cylindrical in form with two wheels of diameter larger than the diameter of the housing supporting the housing on either end. Larger wheels permit the device to more easily travel over small bumps or obstacles and changes in elevation. Furthermore, the design requires less power to drive the housing, so more energy is available for the primary function of vacuuming.

3. Design Specifications

3.1 Objectives

Objectives	
Less time consumption	Quick Drying
Eco-Friendly	Cost Effective
User Friendly	Less Usage of water
No harsh treatment on floor	Battery Powered
Optimum use of chemicals (disinfectants)	Notifying once the work is completed

3.2 Constraints

Constraints	
Water consumption	cleaning dry stains
Controlling Movement of device	Controlling release of water during the movement
Water resistance	

3.3 Objective tree (affinity diagram)

O#	Objectives	First level objectives	Second level objectives	Third level objectives
1	Safety	•		
2	device safety		•	
3	water proof			•
4	rigid frame			•
5	liability litigation			•
6	mode of cleaning	•		
7	brushing		•	
8	scrubbing		•	•
9	wiping		•	•
10	drying		•	
11	maintenance	•		
12	battery maintenance		•	
13	water management	•		
14	Refilling regularly		•	
15	Using clean water		•	
16	brush replacement		•	
17	using disinfectant			•
18	functionality	•		

19	control flow flow		•	
20	operating specification of scrubber			•
21	notification of cleaning		•	

Objective tree:

3.4 Design Specifications:

Si.	Engineering Specifications	Units
1	Overall dimensions	Millimeter
2	Water temperature range	Celsius
3	Speed of bush /scrubber	rpm
4	Amount of water used	Cubic meter
5	Time consumed per wash	Minutes
6	Time consumed for drying	Minutes
7	Electricity consumption	Ampere
8	Gross weight	Kilograms
9	Operation	Semi-automatic

Competitive Benchmarking:

Metric #	Metric	Units	Competitive Products		
			Product 1 (I BELL)	Product 2 (EUFY by Anker)	Product 3 (Ecovacsdeebot 500)
1.	type of floor	type	Hard and soft	Carpet	Wood
2.	Type of moping	wet/dry	wet	wet	dry
3.	Type of control	type	App	voice/remote	app/voice
4.	power mode	type	battery	battery	battery
5.	operator needed for process	yes/no	yes	yes	yes
6.	drying	type	N/A	manual	N/A
7.	dimension	cm	436 X 368 X 11.8	32.5 X 32.5 X 7.2	33.2 X 33 X. 7.9
8.	Cleaning path width	cm	35.8	32.5	33.2

Phase 4

4.1 Concept Generation

4.1 Defining Functions

Si.	Functions	Sub Functions (optional)
1	Wet cleaning of the floor	Stain removing
2	Water resistance of component	
3	Optimum brush speed	Proper cleaning of all parts of the floor
4	Modes of cleaning	
5	Spraying disinfectant	
6	Control of water usage & pressure	Effective cleaning
7	Notify once its done	Notification of every step


4.2 Morphological Chart

Functions ▼	Means ►	Means 1	Means 2	Means 3	Means 4	Means 5
Motion of machine		Straight	Zigzag	Circular	Rotational	
Movement		Programme	Sensors	Bluetooth controlled	Wheels	
Motion of brushes		Rotation	Reciprocating motion	Vibration	Zigzag	
Water dispenser		Inbuilt control	External supply	Sprinkler	Jet spray	
Indication of process		Transparent	Camera	LED indication	User application	
Disinfectant dispenser		Container	Sprinkler	Jet spray	Pre-supply of disinfectant	


4.3 Generating design alternatives

Sketch of generated design concepts/ alternatives:


Design Alternative 1




Design Alternative 2



Design Alternative 3



Design Alternative 4




4.4 Selecting Design Alternative (Using Pugh Chart)

Requirements	Weight	Design1	Design2	Design3	Design4
Safety	10	+	+	+	+
Portability	4	+	-	-	+
Accuracy	8	-	-	+	+
Efficiency	7	+	+	-	+
Cost efficient	8	-	-	+	-
Durability	7	+	-	+	+
Simple user interface	8	-	+	-	+
Power	4	+	-	-	-
Pluses		5	3	4	6
Minuses		3	5	4	2
Overall Total		2	-2	0	4
Weighted Total		27	-9	7	35
Yes / No		No	No	No	Yes


Selected Design Alternative: DESIGN 4

5.1 3D Model


ARDUINO



ULTRASONIC SENSOR




WHEEL




SPRINKLER PIPE




SPRINKLER PUMP




SPINDLE




SPONGE



BALL BEARING HUB





CHASSIS




5.2 Assembly models

Assembly Model






Exploded View




3D Rendered Image




5.3 2D Drawings


(*Note: all dimensions are in mm)




SPRINKLER PUMP




SPRINKLER PIPE




SPINDLE




SPONGE




WHEEL




OUTER CASING



Vacuum Motor



Nozzle



5.4 Design Calculations

Design Calculations

Room Dimensions

Length (assumption) = 4.8 m (L)

Breadth (assumption) = 4.5 m (B)

Calculating the specs of Robot

No. of drive motor = 4

Radius of wheel drive (R) = 50 mm = 0.05 m

RPM of each drive motors (N) = 60 rpm

Width of the Robot = 450 rpm = 0.45 rpm

Speed

$$V = R * \omega$$

$$\omega = (2 * \pi * N) / 60$$

$$= 2 * 3.14 * 60 / 60$$

$$= 6.28 \text{ rad/sec}$$

$$\Rightarrow V = 0.320 \text{ m/s.}$$

Considering efficiency of power delivered to motor = 90%.

$$\begin{aligned} \text{Speed of Robot (V}_r\text{)} &= V * 0.9 \\ &= 0.288 \text{ m/s} \end{aligned}$$

Time taken by the robot to cover the room length at once

$$(t) = L / V_r$$

$$= 4.8 / 0.288$$

$$= 16.6 \text{ secs.}$$

No. of Passes Required for robot to cover the entire room =

$$= \text{Breadth (B)} / \text{width of the robot (w)}$$

$$= 4.5 / 0.45$$

$$= \underline{\underline{10 \text{ Passes}}}$$

Time taken by the robot to cover the entire room =

$$= 16.6 * 10$$

$$= 166 \text{ secs} = 2 \text{ min } 44 \text{ secs.}$$

5.4 Bought out and Manufactured Parts

Bought out parts	Manufactured Parts
● Ultrasonic Sensor ● Arudino ● Wheels ● Dc motor ● Sponge ● Bluetooth module ● Battery ● Ball bearing hub	● Chassis ● Vaccum suction inlet with storage ● Sprinkler pipe ● spindle

6.2 Bill of Materials


Si No	Part Number	Part Name	Quantity	Material Specification
1		Ultrasonic Sensor	4	-----
2		Arduino	1	-----
3		Chassis	1	Mild steel
4		Wheels	4	OEM
5		DC Motor (60rpm)	4	-----
6		DC Motor (600rpm)	1	-----
7		Outer casing with water & dust storage	1	Aluminum
8		Vacuum system	1	-----
9		Sponge	1	OEM
10		Bluetooth module	1	-----
11		Ball bearing hub	1	-----


12		Motor driver	3	----
13		Battery	1	----
14		Sprinkler pump	1	----
15		Sprinkler pipe	1	PVC
16		Spindle	1	Stainless steel

6.3 Joining techniques/ methods:

#	Joining Method	Material to be joined	Resources required and specification
1	Welding	Sheet Metal	40/80 2 sheet MS
3	Adhesives	Acrylic, Metal	M-SEAL


3D model:






FEM Analysis:


1) STATIC STRUCTURAL STRESS ANALYSIS



2) STATIC STRUCTURAL STRAIN ANALYSIS



3) STATIC STRUCTURAL TOTAL DEFORMATION



Analysis details:


Material Type : Aluminum Alloy :- Yield Stress = 90 Mpa

Mesh Type : Tetrahedron – Fine

Boundary Conditions : Water Storage Weight = 2 Kg (Max)

Dust Storage Weight = 0.3 Kg (Max)

Total Load On Chassis = $4.15 * 9.81 = 40.7115 \text{ N}$



RESULT & DISSCUSIONS:

Stress on chassis

$$F = \text{Max load kept on the chassis}$$

$$= 4.15 \times 9.81 \Rightarrow 40.7115 \text{ N}$$

$$\frac{M}{I} = \frac{\sigma}{y} = \frac{E}{R}$$

$$M = Fd$$

$$\Rightarrow 40.7115 \times 0.1 \Rightarrow 4.07115 \text{ N-m}$$

$$I = \frac{bh^3}{12} \Rightarrow \frac{(0.4)(0.002)^3}{12}$$

$$\Rightarrow 2.667 \times 10^{-11} \text{ m}^4$$

$$y = \frac{b}{2} \Rightarrow \frac{0.4}{2}$$

$$\Rightarrow 0.2$$

$$\sigma = \frac{MY}{I} \Rightarrow \frac{4.07115 \times 0.2}{2.667 \times 10^{-11}}$$

$$\Rightarrow 30.808 \text{ MPa}$$


$$FOS = \frac{\text{Max tensile stress}}{\text{calculated stress}} \Rightarrow \frac{49.292}{30.808} \Rightarrow 1.60$$

$\therefore$ The Design is Safe.

$$FOS = 1.6$$

The Design is Safe.


Circuit Diagram:



Product Catalogue:



Product in use:



Operating Instructions:

- Pour required amount of water in the water storage.
- Turn on/off the switch to start/stop cleaning.
- If the sponge gets dirty/torn, remove the above case and replace the sponge with a good one.
- And also clean the dust storage by doing the same as mentioned above


Team Members:



SRIVATSA BELGAUMKAR
ANIRUDH GUDI
SUPREET MUDHOL
DHEERAJSINGH RAJPUT
VIKHYAT GAONKAR
VIJAY KALYANI

Mentors:
Prof. NAGRAJ EKBOTE
Prof. SHRIDHAR M.


Contact:
Srivatsa Belgaumkar
Mob.: 9886786207
E-mail: belsriv@gmail.com



"SMACBOT"

"TIRED OF USING A BROOM,
USE SMACBOT TO HAVE A CLEAN ROOM"

SMART FLOOR MOPPING DEVICE



Experience Engineering @
School of Mechanical
EngineeringKLETECH
Engage | Explore | Excel | Evolve



KLE Technological
University
Creating Value
Leveraging Knowledge

School of Mechanical Engineering

Minor Project Team C7


Introduction:

The major problem faced by Households/ Malls/Hotels and many buildings these days is cleaning of dirty floors, which requires hard work and is also time consuming. This is a Smart Floor Mopping Robot, which is specifically designed to reduce the workload and time taken to clean.

Features:

- Cost effective with respect to existing products
- Does Both Vacuum suction and Mopping
- Semi-automatic
- Rust free
- Auto Obstacle detection and moves accordingly.
- Safe, user friendly operation.

3D Model:



Background/Introduction

It requires less labor work and there is no requirement of skilled labor to operate. This ergonomically designed machine controlled by an arduino uses less water than the manual cleaning methods.

Product Specifications:

- Machine weight: up to 5 Kg
- Time required to clean a room: 5-10mins*
- Water storage : up to 2 liters
- Micro-Controller: Arduino Mega
- Dirt storage: up to 500gms.

*Note: Some of the above mentioned Specifications are the results from the calculations from the best of our knowledge, actual time/units may vary.

Circuit Diagram

